

roto black line



S 110 DC

S 110 DC
S 110 Diamond Cut
7,2 x 45 mm



S 160 SC

S 160 SC
S 160 Strip Cut
6 mm



S 160 CC

S 160 CC
S 160 Cross Cut
4 x 40 mm



S 210 SC

S 210 SC
S 210 Strip Cut
6 mm



S 210 CC

S 210 CC
S 210 Cross Cut
4 x 25 mm

TYPE	S 110 DC	S 160 SC	S 160 CC	S 210 SC	S 210 CC
MODEL	S 110 Diamond Cut 7,2 x 45 mm	S 160 Strip Cut 6 mm	S 160 Cross Cut 4 x 40 mm	S 210 Strip Cut 6 mm	S 210 Cross Cut 4 x 25 mm
	8 sheets/CD/credit card, dual slot w/Emergency Stop Switch – Attached separate CD bin and handle	10 sheets (max. 12 sheets)/CD/credit card, dual slot w/Emergency Stop Switch – Attached separate CD bin	8 sheets (max. 10 sheets)/CD/credit card, dual slot w/Emergency Stop Switch – Attached separate CD bin	16 sheets (max. 20 sheets)/CD/credit card, dual slot w/Rocker Switch – Attached separate CD bin	12 sheets (max. 15 sheets)/CD/credit card, dual slot w/Rocker Switch – Attached separate CD bin
OPENING	223 mm	225 mm	225 mm	230 mm	230 mm
SHRED SIZE	7,2 x 45 mm	6 mm	4 x 40 mm	6 mm	4 x 25 mm
MOTOR	DC motor	Capacitor motor	Capacitor motor	Capacitor motor	Capacitor motor
BIN CAPACITY	15,8 l	19,3 l	19,3 l	39,52 l	39,52 l
SPECIAL FUNCTION	Bin full	LED – Green for Ready, Red for Overheat	Bin full sensor, LED – Green for Ready, Red for Overheat	Bin full sensor, LED – Green for Ready, Orange for door open, Red for Overheat & Overload	Bin full sensor, LED – Green for Ready, Orange for door open & bin full, Red for Overheat & Overload